



Drywall Compound

# Stud Adhesive

For Superior Adhesion

Meet all your plasterboard and interior wall and ceiling fixing needs



# Stud Adhesive

## Description

UPA Stud Adhesive is specially formulated to meet all your plasterboard and interior wall and ceiling fixing needs. The superior formula prevents skinning in the heat and thickening in the cold. The tough flexible bond resists cracking and compensates for minor frame irregularities.

UPA Stud Adhesive gives plasterers the quality and versatility required for plastering jobs.

## Applications

UPA Stud Adhesive should not be applied to wet or green timber. Apply UPA Stud Adhesive in dollops 25mm in diameter and 15mm thick. On walls, dollops to be applied at 230mm centres and 200mm from ends or edges of sheets.

On ceilings, dollops to be applied at 200mm centres and 400mm intervals from edges of sheets.

Plasterboard linings should be pressed firmly against UPA Stud Adhesive within 30 minutes of application. Do not apply adhesive within 200mm of nailing or screwing points. Do not apply adhesive at window or door openings or at butt joints.

Fasten plasterboard in accordance with manufacturer's instructions.

## Advantages

- Superior adhesion quality.
- Fast and easy application.
- Humidity resistant.
- No drips

### UPA Direct

173 Arden Street  
North Melbourne, Victoria 3051 AUSTRALIA  
1300 UPA Direct - 1300 872 347  
Ph: +61 3 9329 2165  
Fax: +61 3 9329 2189